

O²⁰ de-humidifier



20 Ltrs / Day
extraction capacity



Recommended Upto 2500-3500 cu.ft
indicative coverage area



Digital Display
to view / set humidity & temperature



Large Tank Capacity @ 6.5 Ltrs
for longer dehumidification performance



Semi Air Purification
with high quality hepa\carbon filters ensuring clean air at all times



Auto Restart
resumes operation once power comes on



Auto Resume
pre-set humidity levels maintained on power resumption



Extraction (l/24hr) (30°C, 80% RH)	l/24hr	20
Recommended Coverage for dehumidification (Indicative) (Domestic)		Upto 3500 cu.ft. 99 cu.mt.
Recommended Coverage for dehumidification (Indicative) (Industry)		Upfo 2500 cu.ft. 70 cu.mt.
Power consumption, Power supply 220V-240V/50Hz	watts	265
Air Flow		145 m ³ /hr 85 cfm
Noise Level (Approx.)	db	43
Dimensions (W X D X H)	inches	15" x 12" x 23"
Tank Capacity	litres	6.5
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-134a
Empty Weight	kgs	13.5
Running Temperature		5°C – 35°C
Switch Off Timer		Yes
Air Purification		Hepa\Carbon Filter (Optional)
Auto Restart Auto Resume		Available Available
Programmable On Off Timer		Optional


RoHS


Home



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &



Defense